

# BREWART

**GUYSON**


## APPLICATION

- Food hose of latest generation, specifically designed to meet the demanding requirements of the beer processing industry.
- It is suitable for conveying high quality raw, pasteurized and organic beer, alcoholic beverages, soft drinks and wine.
- Delivery and slight suction hose.

## CONSTRUCTION

### TUBE

- BIIR rubber (code 90FDA), light colour, food grade, odourless and tasteless, mirror smooth.
- It complies with FDA Standards, 3-A Sanitary Standards n.18-03-Class II, D.M. 21/03/73 and following amendments.
- Validation by the institute "Technische Universität München WEIHENSTEPHAN".

### REINFORCEMENT

- Plies of synthetic cord.

### COVER

- CR rubber, red colour, resistant to abrasion, ozone and weather, smooth, cloth finish.

## MARKING



## MAIN BENEFITS

- The special structure is free from plasticizers, phthalates and animal derived ingredients, thus reducing the risk of bacterial growth and contamination of the product conveyed.
- The very strong structure makes it perfect for loading and unloading operations in breweries.
- The composition of the cover ensures utmost resistance to aging.
- Hose in accordance with EC 1935/2004 and 2023/2006/EC (GMP).
- The MTG production cycle is free from animal derived ingredients, phthalates, adipates and materials subject to restrictions acc. to EC 1907/2006 (REACH).

## SAFETY FACTOR

- ≥ 3 times working pressure.

## TEMPERATURE RANGE

- From -40°C to +120°C.

## STERILIZATION

- Sterilization up to +130°C for max. 30 minutes.
- In case of long lasting sterilizations we suggest to use the model with vulcanized couplings at the ends.

## TECHNICAL SPECIFICATIONS

SIZE TOLERANCES: I.D.: ISO 1307 - Wall thickness: DIN 7715 T4 S2 - Length: ISO 1307

Inner Diameter mm	Outer diameter mm	Wall thickness mm	Working pressure BAR	Burst pressure BAR	Vacuum BAR	Min. bending radius mm	Approx. weight kg/m	Max. length m
19	29	5	16	48	-0.6	120	0.48	40
25	37	6	16	48	-0.6	150	0.74	40
38	56	9	16	48	-0.6	240	1.85	40
51	71	10	16	48	-0.6	300	2.80	40
63.5	87.5	12	16	48	-0.5	400	3.90	40
76	106	15	16	48	-0.4	450	5.75	40

Other sizes and colours are available upon request. Please contact our Sales Department. Above technical data refer to application at room temperature (+20°C).


**GUYSON INTERNATIONAL LIMITED**
**HOSE & COUPLINGS DIVISION**

Southview Business Park, Guiseley, Leeds LS20 9PR

Tel: 01943 870044 e-mail: leeds@guyson.co.uk web: www.guyson.co.uk



NOTE: All technical information shown is correct at time of print and may be subject to change without notice. For specific applications, please consult Guyson Technical Sales Department.

 FS 28046  
BREWART 0922