

COMPRESSED AIR 20 BAR (300 psi) - STANDARD DUTY



185AA

Compressed air 20 bar (300 psi) - standard duty exceeds DIN 20018/1

Tube: Black synthetic elastomer - oil mist resistant

Reinforcement: High tensile textile cords

Cover: Black synthetic elastomer with longitudinal yellow stripes - abrasion and ozone resistant

Use: Compressed air and general industrial applications

Safety factor: 3:1

Temperature: -10 °C +60 °C (+14 °F +140 °F)

										
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
6	1/4	12	0,51	20	300	48	2,00		0,120	0,085
8	5/16	14	0,59	20	300	64	2,50		0,140	0,095
10	3/8	17	0,67	20	300	80	3,00		0,205	0,140
13	1/2	21	0,83	20	300	104	4,00		0,280	0,190
16	5/8	24	0,98	20	300	128	5,00		0,355	0,240
19	3/4	28	1,10	20	300	152	6,00		0,460	0,310
25	1	35	1,38	20	300	200	8,00		0,640	0,435



GUYSON INTERNATIONAL LIMITED **HOSE & COUPLINGS DIVISION**
Southview Business Park, Guiseley, Leeds LS20 9PR
Tel: 01943 870044 e-mail: leeds@guyson.co.uk web: www.guyson.co.uk

