

STEAM 6 BAR (90 psi) HOT WATER 15 BAR (225 psi) - FDA



350LE

Steam 6 bar (90 psi)

hot water 15 bar (225 psi)

FDA

Tube: White food grade EPDM

Reinforcement: High tensile textile cords


Cover: Blue EPDM - heat, abrasion and ozone resistant

Use: Saturated steam and hot water delivery in general industrial applications.

Specially designed for wash down use in the food and dairy industry

Safety factor: Water 4:1 - Steam 10:1

Temperature: Water -40 °C +120 °C (-40 °F +248 °F)
Steam +165 °C (+330 °F)

										
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
13	1/2	23	0,91	6	90				0,370	0,250
16	5/8	26	1,02	6	90				0,430	0,290
19	3/4	31	1,22	6	90				0,600	0,405
25	1	37	1,46	6	90				0,740	0,500
32	1 1/4	46	1,81	6	90				0,930	0,625
38	1 1/2	52	2,05	6	90				1,090	0,735
51	2	67	2,64	6	90				1,660	1,120



GUYSON INTERNATIONAL LIMITED

HOSE & COUPLINGS DIVISION

Southview Business Park, Guiseley, Leeds LS20 9PR

Tel: 01943 870044 e-mail: leeds@guyson.co.uk web: www.guyson.co.uk

